




Ura


A329821C

LED 1x19W 4000K 1940lm

IMÁGENES / IMAGES / IMAGES



Emisión de luz 1 / CDL polar



Emisión de luz 1 / Diagrama conico

Separación [m]	Diámetro conico [m]	Intensidad luminica [lx]
0.50	30	E(0°) 1151 E(C0) 88.1° 0.52
1.0	60	E(0°) 288 E(C0) 88.1° 0.51
1.5	90	E(0°) 128 E(C0) 88.1° 0.50
2.0	121	E(0°) 72 E(C0) 88.1° 0.50
2.5	151	E(0°) 46 E(C0) 88.1° 0.50
3.0	181	E(0°) 32 E(C0) 88.1° 0.50

TIPO	TYPE	TYPE
Aplique	Wall Lamp	Applique
ACABADO	FINISH	FINITION
Opal/Cromo	Opal/Chrome	Opal/Chrome
MATERIAL	MATERIAL	MATIÈRE
Metal/Metacrilato	Metal/Methacrylate	Métal/Méthacrylate
DETALLES	DETAILS	DÉTAILS

DETALLES / DETAILS / DÉTAILS



COMPONENTS / MAIN PARTS / COMPOSANTS

1 x DRIVER LIFUD :LF-GI022YM0500H 25-40VDC 500mA PF>0'9

1 x PCB 19W 3B13C SANAN 3030 1W 500mA 4000K

MEDIDAS / MEASURES

	Length (mm)	Width (mm)	Height (mm)	KG	Gross (Kg)	Net (Kg)
Box 1	625	90	60	Weight 1	1,35	1,24
Box 2	0	0	0	Weight 2	0,00	0,00